

Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product Name: Flexi-Weld 520 Part A
Product Use: Epoxy Adhesive

Company Identification

Edison Coatings, Inc.
3 Northwest Drive
Plainville, CT 06062

Edison Coatings Tech Info Phone: 1-860-747-2220
Emergency Phone: 1-800-535-5053

2. HAZARDS IDENTIFICATION

Hazard Classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Acute Toxicity – Category 4 - Oral

Skin Irritation – Category 2

Eye Irritation – Category 2A

Skin Sensitization – Category 1

Chronic Hazards to the Aquatic Environment – Category 2

Label Elements

Hazard Pictograms



Signal Word: **WARNING**

Hazards

Causes skin irritation.
Harmful if swallowed.
Causes serious eye irritation.
May cause an allergic skin reaction.
Toxic to aquatic life with long lasting effects.

Precautionary Statements**Prevention**

Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.

Response

IF SWALLOWED: Rinse mouth. Call a POISON CENTER or doctor/physician if unwell.
IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage

Store locked up.

Disposal

Dispose of contents/container to an approved waste disposal plant.

Other Hazards

No data available

3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight%	Chemical Name
Bisphenol A 80-05-7	<30%	4,4'-(propane-2,2-diyl)diphenol
Multi-functional Acrylate Monomer 15625-89-5	<10%	Trimethylolpropanetriacrylate
Alkyl Glycidyl Ether 120547-52-6	<1.0%	Alkyl Glycidyl Ether

4. First Aid Measures

Eye Contact:

Flush eyes with plenty of water for 15 min. while holding eyelids open. Get medical attention.

Skin Contact:

Remove contaminated clothing and wipe excess from skin. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. Contaminated leather articles cannot be decontaminated and should be destroyed to prevent reuse.

Ingestion:

Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

Inhalation:

Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

Medical Conditions Aggravated by Exposure:

Pre-existing eye, skin and respiratory disorders.

5. FIRE FIGHTING MEASURES

Extinguishing Media:

Water fog, Alcohol foam, dry chemical, Carbon Dioxide (CO₂)

Unusual fire and explosion hazards:

None.

Fire Fighting Procedures:

Material will not burn unless preheated. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots) and a positive pressure NIOSH-approved, self-contained breathing apparatus. Cool fire-exposed containers with water.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Use cautious judgment when cleaning up large spills. When dealing with large spills, wear respirator and protective clothing as appropriate. Shut off source of leak if safe to do so. Dike and contain. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand, or other suitable material; dispose of properly. Flush area with water to remove trace residue. When dealing with small spills, take up with an absorbent material and dispose of properly.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures. Handle in accordance with the potential hazard of the curing agent being used. Containers, even those which have been emptied, can contain hazardous product residues. Minimize all contact with material. Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Launder contaminated clothing before reuse. Heating this resin above 300°F in the presence of air may cause low oxidative decomposition. Above 500°F, polymerization may occur. Some curing agents, e.g. aliphatic polyamines, can produce exothermic reactions which in large masses can cause runaway polymerization and charring of the reactants. Fumes and vapors from these thermal and chemical decompositions vary widely in composition and toxicity. Do not breath fumes. Use a NIOSH-approved respirator as required to prevent overexposure. In accord with 20 CFR 1910.134, use either an atmosphere-supplying or an air-purifying respirator for organic vapors.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and Face Protection:

Wear chemical goggles if there is a likelihood of contact with eyes.

Skin Protection:

Wear chemical resistant gloves as required to minimize contact. Wear industry appropriate attire.

Other Personal Protection Data:

Eye wash fountains and safety showers should be available for emergency use. Usual industrial work clothes should be worn.

Respiratory Protection:

Avoid breathing vapor or mists. If exposure may or does exceed occupational exposure limits, use a NIOSH-approved respirator to prevent overexposure.

Ventilation:

Use local exhaust or general dilution ventilation to control exposure within applicable limits.

Exposure Guidelines

There is no data available on either OSHA Permissible Exposure Limits (PEL's) or ACGIH Threshold Limit Value (TLV's) for components of product.

9. PHYSICAL PROPERTIES

Odor:	Normal for this product.
Physical State:	Neutral Liquid
pH:	Not Determined
Vapor Pressure (mmHg):	<1.0
Vapor Density (Air=1):	>1.0
Boiling Point:	Not Determined
Solubility in Water:	Slight
Coefficient of water/oil distribution:	Not Determined
Density (grams per milliliter):	1.10
Evaporation Rate (Ether=1):	Not Determined
Flash Point (Fahrenheit):	>200°F
Flash Point (Celsius):	>93°C
Lower Explosive Limit (%):	Not Determined
Upper Explosive Limit (%):	Not Determined
Autoignition temperature:	Not Determined

10. STABILITY AND REACTIVITY

Stability:	Unstable. Polymerization may occur.
Conditions to Avoid:	Heat, open flame
Incompatibility:	Strong oxidizing agents, polymerization initiators, strong acids, strong bases
Hazardous Polymerization:	May Occur
Hazardous Decomposition Products:	Carbon Monoxide, Carbon Dioxide, Aldehydes, and Acids
Sensitivity to static discharge:	Not determined.

11. TOXICOLOGICAL INFORMATION

Mutagens/Teratogens/Carcinogens:

MUTAGENICITY: DGE BPA, a component of this product, has proved to be inactive when tested by in vivo mutagenicity assays. It has shown activity by in vitro microbial mutagenicity screening and have both produced chromosomal aberrations in cultured rat liver cells. The significance of this information to man is unknown.

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Mix with stoichiometric quantities of curing agent and dispose as common waste.

14. TRANSPORTATION INFORMATION

No information on transportation is available.

15. REGULATORY INFORMATION

The components of this product are listed on the EPA/TSCA Inventory of Chemical Substances.

Protection of stratospheric ozone (pursuant to section 611 of the Clean Air Act Amendments of 1990): Per 40 CFR Part 82, this product does not contain nor was it directly manufactured with any Class I or Class II ozone-depleting substances. The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements, you should contact the appropriate agency in your state.

State Listed Component	Percent	State Code
Epichlorohydrin (CAS NO: 106-89-8)	2 ppm	MA, CA65C/R

CA = California Hazardous Substance list; CA65C, CA65C/R = California Safe Drinking water and toxics Enforcement Act of 1986 or Proposition 65 List; CT = Connecticut Toxic Substance List; FL = Florida Substance List; IL = Illinois Toxic Substance List; LA = Louisiana Hazardous Substance List; MA = Massachusetts Substance List; ME = Maine Hazardous Substance List; MN = Minnesota Hazardous Substance List; NJ = New Jersey Substance List; PA = Pennsylvania Hazardous Substance List; RI = Rhode Island Hazardous Substance List.

California Proposition 65 Footnote: CA65C = The chemical identified with this code is known to the state of California to cause cancer. CA65R = The chemical identified with this code is known to the state of California to cause birth defects or other reproductive harm. CA65C/R = The chemical identified with this code is known to the state of California to cause both cancer and birth defects or other reproductive harm.

16. OTHER INFORMATION

Effective Date: 18/Apr/2016
Revision Date: 29/Sep/2017