



Edison Coatings, Inc.

Restoration Products

Stone, Masonry, Terra Cotta & Historic Concrete Restoration

CUSTOM SYSTEM 45 **Masonry Repair Mortars**

- ◆ Over 3000 formulations in 10 grades, matched to properties, color, texture and appearance of natural stone, terra cotta, brick, stucco and concrete; Custom colors available.
- ◆ Hand-apply, carve, sculpt, cast-in-place, tool or extrude
- ◆ 30 years of successful performance on thousands of historic buildings and monuments

RL-Series Restoration **Latex Admixtures**

- ◆ Mix with Custom System 45, or improve adhesion and mechanical properties of other cement-based mortars
- ◆ Multiple grades are available:
 - RL-1 for hand-applied, non-sag patching
 - RL-2 for highly fluid casting or coating mixes
 - RL-3 for marine/immersion exposures
 - RL-4 for high permeability applications
 - RL-5 to extend working times in hot weather
 - RL-6 for faster setting in cold weather
 - RL-7 for sculpting and extended working time

THIN-FILL 55 **Thin-Section Reprofiling Mortar**

- ◆ Ultra-fine cement-based mortar for filling thin-section glaze spalls and for creating smooth, fluted or complex profiles.
- ◆ Easily sanded to achieve ultra-smooth surfaces.

Traditional Mortars, Stuccos, Cements & Historic Concrete Materials

ROSENDALE Natural Cement Products®

- ◆ Authentic historic materials used in construction of thousands of buildings and structures in the 19th and early 20th centuries.

10C: Natural Cement
11G: Grouts
12M: Mortars
13P: Patching
14S: Stucco
15W: Whitewash
16B: Concrete
17L: Hydraulic Lime

- ◆ Support, Training, and color-matching services available.
- ◆ Exceptional durability, compatibility, sustainability.

SPEC-JOINT 46 **Masonry Mortars**

- ◆ Lime and Cement/Lime Based prepackaged mortars incorporate custom aggregate blends and colors to match existing, historic mortars.
- ◆ ASTM C270 Types M, S, N, O and K.
- ◆ Historic Lime Type L Mortar

- ◆ Traditional masonry mortars, for repointing or rebuilding, require only addition of water before use.

LP20 Lime Putty, 20M Lime Putty Mortar, 20S Lime Putty Stucco

- ◆ Lime Putty and Prepackaged, custom-colored lime putty-based mortars and stuccos.

CEM-PLAST 54 **Portland Cement Plasters & Stuccos**

- ◆ Prepackaged, custom-colored ASTM C926 stucco systems.

Weatherproof & Decorative Coatings

EVERKOTE 300 **Mineral Coatings**

- ◆ Inorganic, reactive mineral silicate provide natural finishes, 99% breathability and exceptional durability.
- ◆ Available in 3 grades:
Penetral stains
Patinar paints
Textur textured finishes

ELASTOWALL 351, **ELASTO-TONE 353** **Breathable Coatings**

- ◆ Highly permeable (30-40 perms), permanently flexible coatings decorate and weatherproof in one step.
- ◆ Bridge working cracks, withstand wind-driven rain, remain flexible at low temperatures.
- ◆ Over 25 years of performance success on historic buildings.

EXPO 43 Latex/Cement **Based Coating**

- ◆ Natural color and texture finishes to coat concrete, sandstone, limestone and stucco.
- ◆ Expo 43 cement-based coatings can be color-coordinated with Custom System 45 patching compounds.

AQRYL-X 200 **Very Low VOC Coating**

- ◆ Highly durable, vapor-permeable self-crosslinking 100% acrylic coatings produced in Clear and 900 standard stain colors, with custom color-matching available.

SYSTEM 90-Series **Stains, Consolidants** **and Weatherproofing**

- ◆ Highly durable, vapor-permeable weatherproofing sealers and consolidants.
- ◆ Multiple Grades:
90W Clear Waterborne
90WL Light-Color Surfaces
90W-Color Stains
90-II Light Consolidants

LIQUIDIRT 94

- ◆ Semi-transparent stains are matched to soil, carbon and rust colors; can be applied to newly repaired or repointed surfaces to provide aged, weathered appearance.

AQUATHANE UA210 **Glaze Replacement &** **Anti-Graffiti Coatings**

- ◆ Exceptionally durable, color stable, breathable waterborne aliphatic polyurethane coatings are matched to gloss, color and depth of terra cotta and brick glazes.
- ◆ Appearance: 900 standard colors plus Clear; Opaque or Translucent; Gloss, Satin and Flat finishes
- ◆ Available in chemical-resistant (H) and anti-graffiti (A/G) grades, standard grade (NCL) and 2 elastomeric grades (E, EE)

AQUASPEX 220 **Multi-Color Special** **Effects Coatings**

- ◆ Clear, durable waterborne coatings incorporate specks of various sizes and colors to replicate speckled terra cotta glazes and granite faux finishes

SILOX-TREAT 89W, **89WH**

- ◆ Waterborne, breathable water-repellent treatments

Concrete Repair & Resurfacing

SYSTEM 22 **Surface Set Retarder**

- ◆ Mist-applied retarder facilitates exposed aggregate repairs to concrete and stucco.

SYSTEM 44 **Structural Concrete Repair Mortar**

- ◆ One-component, polymer-modified mortars in Regular and Fast-Setting formulations.
- ◆ Vertical/Overhead, Horizontal/Pourable grades.

DECK-TOP 47 **Concrete Repair & Resurfacing**

- ◆ High-strength latex-modified mortar is applied in any depth from 1/8" (3 mm) to several inches.
- ◆ May be used to alter surface pitch and/or impart slip resistance to traffic-bearing surfaces.
- ◆ Available in Standard Grey or Custom Colors.

SYSTEM 49 CPBA **Corrosion Inhibiting Primer**

- ◆ Latex-modified cement-based slurry for protection of reinforcing steel, applied prior to patching

LEVEL-X52, 52-XT Self-Leveling Toppings

- ◆ One-component, high-strength polymer-modified cement-based toppings for leveling and resurfacing rough, scaled concrete.
- ◆ Applied in depths from 1/8" (3 mm) to several inches, withstand heavy traffic. Exterior grade (XT) withstands wet exposures.

Crack Repair & Adhesives

PUMP-X53 Series Injection Grouts

- ◆ Pumpable cement and lime-based grouts fill non-working cracks and voids.
- ◆ Available in grades of varying composition, hardness and fineness.

FLEXI-SEAL 510, 510-U **Flexible Epoxy Crack Sealants**

- ◆ 100% solids urethane-modified epoxies seal small working cracks.
- ◆ Low viscosity allows deep penetration by gravity flow or pressure injection.

FLEXI-WELD 520, 520T Masonry Adhesives

- ◆ Fast-setting, 100% solids adhesives.
- ◆ Low viscosity 520 grade is used for crack injection.
- ◆ Thixotropic 520T gel grade is used as a stone-to-stone adhesive and for setting anchors and pins.

FLEXI-FILL 530 **Flexible Epoxy Paste Filler**

- ◆ Flexible, 100% solids paste adhesive in non-sag consistency is used for filling cracks and small chips in stone and masonry surfaces.
- ◆ Custom colors available. Readily accepts addition of fine stone aggregates for aesthetic repair.
- ◆ May be used from 20 below zero to 100 degrees Fahrenheit.

FLASHEPOXY 580 Low Temperature Adhesive

- ◆ For fast-setting and low temperature (-20F) repairs.

Edison Coatings, Inc.

3 Northwest Drive, Plainville, CT 06062

Phone: (860) 747-2220 or (800) 341-6621

E-mail: edison@edisoncoatings.com

Fax: (860) 747-2280 or (866) 658-1189

Internet: www.edisoncoatings.com

Edison Coatings products are for commercial use only. In case of defect in manufacture or packaging, materials will be replaced at no cost. No other warranty, except for such replacement, express or implied, is in effect. Any implied warranty of merchantability or fitness for a particular purpose is expressly disclaimed. Although information and advice supplied in this publication are believed to be reliable, they do not represent performance specifications and no obligation or liability is assumed for advice given or results obtained. Product formulations and performance characteristics are subject to change without notice. Other conditions and limitations may be imposed at time of sale.